

# Technical Specification CE

<b>Spare parts</b>	Replaces	
<b>Ersatzteile</b>	Ersetzt	
<b>Pièces détachées</b>	Remplace	
<b>Reserve onderdelen</b>	Vervangt	
<b>Repuestos</b>	Reemplaza	
<b>Reservdelar</b>	Ersätter	106 25 16-65



	Displacement Hubraum Cilindree Clindrata Slagvolym	Bore Bohrung Alésage Diametro de cilindro Cylinderdiameter	Stroke Hub Course Carrera Slaglängd	Max power of speed Höchstleistung bei Potencia máxima a Max effekt vid	Killing speed Höchstdrehzahl Régime de ralenti Tomgångsvarvtal	Engagement Engeldrehzahl Régime d'embrayage Régimen de acoplamiento Ingreppvarvtal	No load free speed Höchstzahl Nombre de tours max. A maxima revolucion Max rusvarvtal	Spark plug Zündkerze Bougie Bujía Tändstift	Electrode gap Elektrodenabstand Écartement des électrodes Distancia entre electrodos Elektrodstånd	Ignition system Zündanlage Système d'allumage Sistema de encendido Tändsystem	Air gap Luftspalt Écartement Distancia Luftgap	Type of carburetor and setting Vergaser typ und Einstellung Carburateur et réglage Carburador y reglaje Förgasartyp och inställning	Fuel tank volume Füllmenge des Kraftstofftanks Débit du réservoir de carburant Capacidad del tanque de combustible Tankvolym bränsle	Oil pump capacity Ölpumpkapazität Débit de la pompe à huile Capacidad de la bomba de aceite Kapacitet oljepump	Oil tank volume Füllmenge des Öltanks Débit du réservoir d'huile Capacidad del tanque de aceite Tankvolym kedjeolja	Bar length Schwenslänge Longueur de guide Longitud de la espada Svärödlängd	Chain speed Kettengeschwindigkeit Vitesse de chaîne Velocidad de la cadena Kedjehastighet	Chain pitch Kettenteilung Pas de chaîne Peso de la cadena Kedjedehning	Drive link gauge Teilglieder Mailles Eslabones Spårvidd	Weight Gewicht Poids Peso Vikt	Rated voltage Netzspannung Tension nominale Voltaje de régimen Märkspänning	
	cc	Ø mm	mm	kW rpm	rpm	rpm	rpm	NGK Champion	mm	type	mm	type	set.*	liters	ml/min (9 000rpm)	liters	inch	m/sec	inch	mm	kg	volt
315 Electric	—	—	—	1.5 / 7 700	—	—	—	—	—	—	—	—	—	—	5 (7 700)	0.10	14"-16"	14.0	3/8"	1.3	3.8	220 - 240
316 Electric	—	—	—	1.6 / 7 500	—	—	—	—	—	—	—	—	—	—	5 (7 500)	0.10	12"-16"	14.0	3/8"	1.3	3.7	110 - 120
318 Electric	—	—	—	1.8 / 7 500	—	—	—	—	—	—	—	—	—	—	5 (7 500)	0.10	14"-16"	14.0	3/8"	1.3	3.8	230
334T	35.2	38	31	1.5 / 9 600	2 800	4 100	13 800	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA CIQ-EL19	—	0.30	3-7	0.16	12"-14"	18.3	3/8"	1.3	3.4	—
338XPT	39.0	40	31	1.7 / 9 600	2 800	4 100	13 800	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA CIQ-EL19	—	0.30	3-7	0.16	12"-16"	18.3	3/8"	1.3	3.4	—
336	35.2	38	31	1.5 / 9 600	2 800	4 100	13 800	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA CIQ-EL20	—	0.36	3-7	0.20	13"-16"	18.3	.325"	1.3	3.8	—
339XP	39.0	40	31	1.7 / 9 600	2 800	4 100	13 800	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA CIQ-EL20	—	0.36	3-7	0.20	13"-18"	18.3	.325"	1.3	3.8	—
136	36.3	38	32	1.6 / 9 000	3 000	4 500	13 000	BPMR 7A RCI 7Y	0.5	PHELON CD	0.3	WALBRO WT 542	H = 1 1/4 L = 1 1/4	0.41	8	0.20	13"-15"	16.3	.325"	1.3	4.6	—
141	40.2	40	32	1.9 / 9 000	3 000	4 500	13 000	BPMR 7A RCI 7Y	0.5	PHELON CD	0.3	WALBRO WT 542	H = 1 1/4 L = 1 1/4	0.41	8	0.20	13"-15"	16.3	.325"	1.3	4.6	—
340	40.8	40	32	2.0 / 9 000	2 700	3 800	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 195	H = 1 L = 1	0.50	9	0.25	13"-20"	17.3	.325"	1.3 1.5	4.7	—
345	45.0	42	32	2.2 / 9 000	2 700	3 800	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 195	H = 1 L = 1	0.50	9	0.25	13"-20"	17.3	.325"	1.3 1.5	4.7	—
346XP	45.0	42	32	2.5 / 9 600	2 700	3 800	14 200	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL17	H = 1 L = 1	0.50	5-12	0.28	13"-20"	18.5	.325"	1.3 1.5	4.8	—
350	49.4	44	32	2.3 / 9 000	2 700	3 800	13 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 195	H = 1 L = 1	0.50	5-12	0.26	13"-20"	17.3	.325"	1.3 1.5	4.8	—
353	51.7	45	32	2.4 / 9 000	2 700	3 800	13 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL17	H = 1 L = 1	0.50	5-12	0.28	13"-20"	17.3	.325"	1.3 1.5	5.0	—
55	53.2	46	32	2.4 / 9 000	2 500	3 600	12 500	BPMR 7A RCI 7Y	0.5	FHP ET	0.3	ZAMA CIQ-EL6	H = 1 L = 1	0.60	9	0.30	13"-20"	17.4	.325" / 3/8"	1.3 1.5	5.2	—
357XP	56.5	46	34	3.2 / 9 600	2 700	3 700	14 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 198	H = 1 L = 1	0.68	6-17	0.38	13"-24"	21.4	.325" / 3/8"	1.3 1.5	5.5	—
359	59.0	47	34	2.9 / 9 000	2 700	3 700	13 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 198	H = 1 L = 1	0.68	6-17	0.38	13"-24"	21.4	.325" / 3/8"	1.3 1.5	5.5	—
61	61.5	48	34	2.9 / 8 300	2 600	3 700	12 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 254 B	H = 1 L = 1	0.75	5-18	0.45	15"-20"	18.4	3/8"	1.5	6.1	—
362XP Special	62.4	47	36	3.4 / 9 600	2 700	3 600	13 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HD 6B	H = 1 1/4 L = 1 1/4	0.77	4-20	0.42	13"-24"	21.4	.325" / 3/8"	1.5	6.0	—
365 Special	65.1	48	36	3.4 / 9 300	2 700	3 600	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3M-EL2C	H = 1 1/4 L = 1 1/4	0.77	4-20	0.42	15"-28"	20.7	3/8"	1.5	6.0	—
268	66.7	50	34	3.2 / 9 000	2 600	3 500	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 260A	H = 1 L = 1	0.75	5-18	0.45	15"-20"	20.0	3/8"	1.5	6.2	—
372XP	70.7	50	36	3.9 / 9 600	2 700	3 600	13 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HD 6B	H = 1 1/4 L = 1 1/4	0.77	4-20	0.42	15"-28"	21.4	3/8"	1.5	6.1	—
281XP	80.7	52	38	4.2 / 9 000	2 500	3 400	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 228C	H = 1 L = 1	0.90	12-16 20-24	0.50	15"-28"	20.0	3/8"	1.5	7.5	—
385XP	84.7	54	37	4.6 / 9 600	2 700	3 600	13 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 299A	H = 1 1/4 L = 1 1/4	0.90	4-20	0.50	18"-28"	21.4	3/8"	1.5	7.0	—
288XP	87.0	54	38	4.5 / 9 300	2 500	3 400	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 228C	H = 1 L = 1	0.90	12-16 20-24	0.50	15"-28"	20.7	3/8"	1.5	7.5	—
395XP	93.6	56	38	4.9 / 8 700	2 500	3 400	12 500	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 300A	H = 1 1/2 L = 1 1/4	0.90	14-21	0.50	18"-36"	19.6	3/8" / .404"	1.5 1.6	7.9	—
3120XP	118.8	60	42	6.2 / 9 000	2 500	3 400	12 000	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO WG 8	L = 1	1.25	28-51	0.70	24"-42"	20.1	.404"	1.6	10.4	—
371K	70.7	50	36	3.5 / 9 800	2 500	3 600	9 800	BPMR 7A RCI 7Y	0.5	FHP CD	0.3	WALBRO HD 20	H = 1 L = 1	0.77	—	—	—	—	—	—	12" 9.1 14" 9.4	—
3120K	118.8	60	42	5.8 / 9 750	2 500	3 400	9 800	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO WG 9	L = 1 1/4	1.25	—	—	—	—	—	—	14" 13.2 16" 14.0	—