

Technical Specification CE

| | | |
|---------------------------|-----------|--------------|
| Spare parts | Replaces | |
| Ersatzteile | Ersetzt | |
| Pièces détachées | Remplace | |
| Reserve onderdelen | Vervangt | |
| Repuestos | Reemplaza | |
| Reservdelar | Ersätter | 544 06 30-01 |



| | Displacement Hubraum Cylindrée Cilindrada Şaqovm | Bore Bohrung Alésage Diámetro de cilindro Cylinderdiameter | Stroke Hub Course Carerra Slaglängd | Max power at speed Höchstleistung bei Puissance max. à Potencia máxima a Max effekt vid | Idle speed Leerlaufdrehzahl Régime de ralenti Régimen de ralentí Tomingsvarvital | Engagement Eingriffsdrehzahl Régime d'embrayage Régimen de aceleramiento Ingreppvarvital | No load free speed Höchstzahl Nombre de tours max. A máxima revolución Max rusrvarvital | Spark plug Zündkerze Bougie Tiedstift | Electrode gap Elektrodenabstand Écartement des électrodes Distancia entre electrodos Elektrodenstand | Ignition system Zündanlage Système d'allumage Sistema de encendido Tändsystem | Air gap Luftspalt Écartement Distancia Luftgap | Type of carburettor and setting Vergetyp und Einstellung Carburateur et réglage Carburador y réglaje Förgärsstyp och inställning | Fuel tank volume Füllmenge des Kraftstofftanks Débit du réservoir de carburant Capacidad del tanque de combustible Tankvolym bränsle | Oil pump capacity Ölpumpkapazität Débit de la pompe à huile Capacidad del tanque de aceite Kapacitet oljepump | Oil tank volume Füllmenge des Öltanks Débit du réservoir d'huile Capacidad del tanque de aceite Tankvolym kedjolja | Bar length Schienenlänge Longueur de guide Longitud de la espasa Kedjelängd | Chain speed Kettengeschwindigkeit Vitesse de chaîne Velocidad de la cadena Kedjelastighet | Chain pitch Kettenteilung Pas de chaîne Paso de la cadena Kedjodelning | Drive link gauge Tredglödler Målårens Eskelonnus Spårvidd | Weight Gewicht Poids Peso Vikt | Rated voltage Netzspannung Tensión nominal Volaje de régimen Märkspänning | Heated handle / carburettor heating Beheizte Handgriffe / Vergaserheizung Calentador de la manija / Calefacción eléctrica del carburador Pajapas chauffantes / Chauffage électrique du carburateur Handgriparms / Förgärsvarme | | |
|--------------|--|--|---|---|--|--|--|--|--|---|--|--|---|---|---|---|---|--|---|--|---|--|---|---------|
| | cc | Ø mm | mm | kW rpm | rpm | rpm | rpm | Husqvarna Champion | mm | type | mm | type | liters | ml/min (9 000rpm) | liters | inch | m/sec | inch | mm | kg | volt | • / • | | |
| 317 Electric | — | — | — | 1.7 | — | — | — | — | — | — | — | — | — | 5 (7 700) | 0.10 | 14"-16" | 14.0 | 3/8" | 1.3 | 4.4 | 230 | — | | |
| 321 Electric | — | — | — | 2.0 | — | — | — | — | — | — | — | — | — | 5 (7 500) | 0.10 | 14"-16" | 14.0 | 3/8" | 1.3 | 4.4 | 230 | — | | |
| 334T | 35.2 | 38 | 31.0 | 1.5 / 9 600 | 2 800 | 4 100 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1Q-EL33A | — | 0.34 | 3-7 | 0.15 | 12"-14" | 18.3 | 3/8" | 1.3 | 3.5 | — | — |
| 338XPT | 39.0 | 40 | 31.0 | 1.7 / 9 600 | 2 800 | 4 100 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1Q-EL33A | — | 0.34 | 3-7 | 0.15 | 12"-16" | 18.3 | 3/8" | 1.3 | 3.5 | — | — |
| 336 | 35.2 | 38 | 31.0 | 1.5 / 9 600 | 2 800 | 4 100 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1Q-EL20B | — | 0.36 | 3-7 | 0.16 | 13"-16" | 18.3 | .325" | 1.3 | 3.9 | — | — |
| 339XP | 39.0 | 40 | 31.0 | 1.7 / 9 600 | 2 800 | 4 100 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1Q-EL20B | — | 0.36 | 3-7 | 0.16 | 13"-18" | 18.3 | .325" | 1.3 | 3.9 | — | — |
| 137 e-series | 36.3 | 38 | 32.0 | 1.6 / 9 000 | 3 000 | 4 500 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | IIDA | 0.3 | ZAMA W29 | — | 0.41 | 8 | 0.20 | 13"-15" | 16.3 | .325" | 1.3 | 4.6 | — | — |
| 142 e-series | 40.2 | 40 | 32.0 | 1.9 / 9 000 | 3 000 | 4 500 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | IIDA | 0.3 | ZAMA W29 | — | 0.41 | 8 | 0.20 | 13"-15" | 16.3 | .325" | 1.3 | 4.6 | — | — |
| 340 | 40.8 | 40 | 32.5 | 2.0 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL18B | — | 0.50 | 9 | 0.25 | 13"-18" | 17.3 | .325" | 1.3 1.5 | 4.7 | — | — |
| 340 e-series | 40.8 | 40 | 32.5 | 2.0 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL32 | — | 0.50 | 9 | 0.25 | 13"-18" | 17.3 | .325" | 1.3 1.5 | 4.8 | — | — |
| 345 e-series | 45.0 | 42 | 32.5 | 2.2 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL32 | — | 0.50 | 9 | 0.25 | 13"-18" | 17.3 | .325" | 1.3 1.5 | 4.8 | — | — |
| 346XP | 45.0 | 42 | 32.5 | 2.5 / 9 600 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL18B | — | 0.50 | 5-12 | 0.28 | 13"-20" | 18.5 | .325" | 1.3 1.5 | 4.8 | — | • / (•) |
| 350 | 49.4 | 44 | 32.5 | 2.3 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL32 | — | 0.50 | 5-12 | 0.25 | 13"-18" | 17.3 | .325" | 1.3 1.5 | 4.8 | — | — |
| 353 | 51.7 | 45 | 32.5 | 2.4 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C3-EL18B | — | 0.50 | 5-12 | 0.28 | 13"-20" | 17.3 | .325" | 1.3 1.5 | 5.0 | — | • / (•) |
| 55 | 53.2 | 46 | 32 | 2.5 / 9 000 | 2 500 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | FHP ET | 0.3 | ZAMA C1Q-EL7 | — | 0.60 | 9 | 0.30 | 13"-20" | 17.4 | .325" / 3/8" | 1.3 1.5 | 5.2 | — | — |
| 455 Rancher | 55.5 | 47 | 32 | 2.6 / 9 000 | 2 700 | 3 800 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO WTA29A | — | 0.44 | 11-12 | 0.32 | 13"-20" | 17.4 | .325" | 1.5 | 5.8 | — | — |
| 357XP | 56.5 | 46 | 34.0 | 3.2 / 9 600 | 2 700 | 3 700 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HDA 199A | — | 0.68 | 6-17 | 0.38 | 13"-24" | 21.4 | .325" / 3/8" | 1.3 1.5 | 5.5 | — | • / • |
| 359 | 59.0 | 47 | 34.0 | 2.9 / 9 000 | 2 700 | 3 700 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HDA 199A | — | 0.68 | 6-17 | 0.38 | 13"-24" | 20.0 | .325" / 3/8" | 1.3 1.5 | 5.5 | — | • / • |
| 365 Special | 65.1 | 48 | 36.0 | 3.2 / 9 600 | 2 700 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HD 12B | — | 0.77 | 6-24 | 0.42 | 15"-28" | 20.7 | 3/8" | 1.5 | 6.0 | — | — |
| 570 | 67.9 | 48 | 36.0 | 3.6 / 9 600 | 2 700 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1M-EL28A | — | 0.70 | 5-22 | 0.37 | 16"-28" | 21.4 | 3/8" | 1.5 | 6.7 | — | — |
| 372XP | 70.7 | 50 | 36.0 | 3.9 / 9 600 | 2 700 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HD 12B | — | 0.70 | 5-22 | 0.37 | 16"-28" | 21.4 | 3/8" | 1.5 | 6.7 | — | • / • |
| 575XP | 73.5 | 51 | 36.0 | 4.0 / 9 600 | 2 700 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | ZAMA C1M-EL28A | — | 0.70 | 5-22 | 0.37 | 16"-28" | 21.4 | 3/8" | 1.5 | 6.8 | — | • / • |
| 385XP | 84.7 | 54 | 37.0 | 4.6 / 9 600 | 2 700 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | TILLOTSON HS 296A | — | 0.90 | 6-24 | 0.50 | 18"-28" | 21.4 | 3/8" | 1.5 | 7.0 | — | • / • |
| 395XP | 93.6 | 56 | 38.0 | 4.9 / 8 700 | 2 500 | 3 400 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | TILLOTSON HS 298A | — | 0.90 | 15-20 | 0.50 | 18"-36" | 19.6 | 3/8" / .404" | 1.5 1.6 | 7.9 | — | • / • |
| 3120XP | 118.8 | 60 | 42.0 | 6.2 / 9 000 | 2 500 | 3 400 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO WG 8 | — | 1.25 | 30-54 | 0.70 | 24"-42" | 20.1 | .404" | 1.6 | 10.4 | — | — |
| 371K | 70.7 | 50 | 36.0 | 3.5 / 9 000 | 2 500 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HD 30 | — | 0.77 | — | — | — | — | — | — | 12" 9.4 14" 9.7 | — | — |
| 375K | 74.7 | 51 | 36.0 | 3.7 / 9 000 | 2 500 | 3 600 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO HD 30 | — | 0.77 | — | — | — | — | — | — | 14" 9.7 | — | — |
| 3120K | 118.8 | 60 | 42.0 | 5.8 / 9 000 | 2 500 | 3 400 | — | PR 17Y | BPMR 7 A RCI 7Y | 0.5 | SEM CD | 0.3 | WALBRO WG 9 | — | 1.25 | — | — | — | — | — | — | 14" 13.2 16" 14.0 | — | — |

Technical Specification 2006 Chain saws, Power cutters

Do not exceed the max no load free speed or engine damage may occur. This figure is for broken in unit. Reduce rpm by 600-700 rpm for a new product.
† See owners manual and service bulletin.
(*) Available only in some markets.
We recommend Husqvarna 2T-fuel and Husqvarna XP-oil.