

Technical Specification for countries outside EPA, CE

Spare parts	Replaces	
Ersatzteile	Ersetzt	
Pièces détachées	Remplace	
Reserve onderdelen	Vervangt	
Repuestos	Reemplaza	
Reservdelar	Ersätter	544 06 32-01



	Displacement Hubraum Cilindrada Slagvolum	Bore Bohrung Diámetro de cilindro Cylinderdiameter	Stroke Hub Carrera Slaglängd	Max power of speed Höchstleistung bei Puissance max à Potencia máxima a Max effekt vid	Idle speed Leerlaufdrehzahl Régime de ralenti Regimen de ralentí Tomningsvarvtal	Engagement Eingriffsdrehzahl Régime d'embrayage Regimen de acoplamiento Ingreppvarvtal	No load free speed Höchstleertourzahl Nombre de tours max. A máxima revolución Max rusvarvtal	Spark plug Zündkerze Bujía Tändstift	Electrode gap Elektrodenabstand Écartement des électrodes Distancia entre electrodos Elektrodesstånd	Ignition system Zündanlage Système d'allumage Sistema de encendido Tändsystem	Air gap Luftspalt Ecartement Distancia Luftgap	Type of carburettor and setting Vergasertyp und Einstellung Carburateur et réglage Carburador y reglaje Förgasertyp och inställning	Fuel tank volume Füllmenge des Kraftstofftanks Débit du réservoir de carburant Capacidad del tanque de combustible Tankvolum bränsle	Oil pump capacity Ölpumpkapazität Débit de la pompe à huile Capacité de la pompe de aceite Kapacitet oljepump	Oil tank volume Füllmenge des Öltank Débit du réservoir d'huile Capacidad del tanque de aceite Tankvolum kedjolja	Bar length Schienenlänge Longueur de guide Longitud de la espada Svärslängd	Chain speed Kettengeschwindigkeit Vitesse de chaîne Velocidad de la cadena Kedjehastighet	Chain pitch Kettenschritt Pas de chaîne Paso de la cadena Kedjebredning	Drive link gauge Triebglieder Maillon Eslabones Spårvidd	Weight Gewicht Poids Peso Vikt	Rated voltage Netzspannung Tension nominale Volaje de régimen Märkspänning	Heated handles / carburettor heating Beheizte Handgriffe / Vergaserbeheizung Calentador de los mangos / Calentador eléctrico del carburador Pogreves chauffantes / Chauffage électrique du carburateur Handgripsvärme / Förgasvärme		
	cc	Ø mm	mm	kW rpm	rpm	rpm	rpm	Husqvarna Champion	mm	type	mm	type	liters	ml/min (@ 000rpm)	liters	inch	m/sec	inch	mm	kg	volt	•/•		
317Electric	—	—	—	1.7	—	—	—	—	—	—	—	—	—	5 (7 700)	0.10	14"-16"	14.0	3/8"	1.3	4.4	230	—		
321Electric	—	—	—	2.0	—	—	—	—	—	—	—	—	—	5 (7 500)	0.10	14"-16"	14.0	3/8"	1.3	4.4	230	—		
334T	35.2	38	31.0	1.5 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1Q-EL33A	↑	0.34	3-7	0.15	12"-14"	18.3	3/8"	1.3	3.5	—	—
338XPT	39.0	40	31.0	1.7 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1Q-EL33A	↑	0.34	3-7	0.15	12"-16"	18.3	3/8"	1.3	3.5	—	—
336	35.2	38	31.0	1.5 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1Q-EL20B	↑	0.36	3-7	0.16	13"-16"	18.3	.325"	1.3	3.9	—	—
339XP	39.0	40	31.0	1.7 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1Q-EL20B	↑	0.36	3-7	0.16	13"-18"	18.3	.325"	1.3	3.9	—	—
137 e-series	36.3	38	32.0	1.6 / 9 000	3 000	4 500	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	IIDA	0.3	ZAMA W29	↑	0.41	8	0.20	13"-15"	16.3	.325"	1.3	4.6	—	—
142 e-series	40.2	40	32.0	1.9 / 9 000	3 000	4 500	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	IIDA	0.3	ZAMA W29	↑	0.41	8	0.20	13"-15"	16.3	.325"	1.3	4.6	—	—
340/340 e-series	40.8	40	32.5	2.0 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL18B C3-EL32	↑	0.50	9	0.25	13"-20"	17.3	.325"	1.3 1.5	4.7/4.8	—	—
345 e-series	45.0	42	32.5	2.2 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL32	↑	0.50	9	0.25	13"-20"	17.3	.325"	1.3 1.5	4.8	—	—
346XP	45.0	42	32.5	2.5 / 9 600	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL18B	↑	0.50	5-12	0.28	13"-20"	18.5	.325"	1.3 1.5	4.8	—	•/(•)
350	49.4	44	32.5	2.3 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL32	↑	0.50	5-12	0.25	13"-20"	17.3	.325"	1.3 1.5	4.8	—	—
353	51.7	45	32.5	2.4 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3-EL18B	↑	0.50	5-12	0.28	13"-20"	17.3	.325"	1.3 1.5	5.0	—	•/(•)
55	53.2	46	32.0	2.5 / 9 000	2 500	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	FHP ET	0.3	ZAMA C1Q-EL6	↑	0.60	9	0.30	13"-20"	17.4	.325"/3/8"	1.3 1.5	5.2	—	—
455 Rancher	55.5	47	32	2.6 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO WTA29A	↑	0.44	11-12	0.32	13"-20"	17.4	.325"	1.5	5.8	—	—
357XP	56.5	46	34.0	3.2 / 9 600	2 700	3 700	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 198A	↑	0.68	6-17	0.38	13"-24"	21.4	.325"/3/8"	1.3 1.5	5.5	—	•/•
359	59.0	47	34.0	2.9 / 9 000	2 700	3 700	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HDA 198A	↑	0.68	6-17	0.38	13"-24"	20.0	.325"/3/8"	1.3 1.5	5.5	—	•/•
61	61.5	48	34.0	2.9 / 8 300	2 600	3 700	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM ET	0.3	TILLOTSON HS 254 B	↑	0.75	5-18	0.45	15"-28"	18.4	3/8"	1.5	6.1	—	—
365 Special	65.1	48	36.0	3.4 / 9 300	2 700	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C3M-EL2C	↑	0.77	6-24	0.42	15"-28"	20.7	3/8"	1.5	6.0	—	—
268	66.7	50	34.0	3.2 / 9 000	2 600	3 500	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	FHP ET	0.3	TILLOTSON HS 260A	↑	0.75	5-18	0.45	15"-28"	20.0	3/8"	1.5	6.2	—	—
570	67.9	48	36.0	3.6 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1M-EL28A	↑	0.70	5-22	0.37	16"-28"	21.4	3/8"	1.5	6.7	—	—
372XP	70.7	50	36.0	3.9 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HD 6B	↑	0.77	6-24	0.42	15"-28"	21.4	3/8"	1.5	6.1	—	•/•
575XP	73.5	51	36.0	4.0 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	ZAMA C1M-EL28A	↑	0.70	5-22	0.37	16"-28"	21.4	3/8"	1.5	6.8	—	•/•
281XP	80.7	52	38.0	4.2 / 9 000	2 500	3 400	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 228C	↑	0.90	14-27	0.50	15"-28"	20.0	3/8"	1.5	7.5	—	—
385XP	84.7	54	37.0	4.6 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 296	↑	0.90	6-24	0.50	18"-28"	21.4	3/8"	1.5	7.0	—	•/•
288XP	87.0	54	38.0	4.5 / 9 300	2 500	3 400	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 228C	↑	0.90	14-27	0.50	15"-28"	20.7	3/8"	1.5	7.5	—	—
395XP	93.6	56	38.0	4.9 / 8 700	2 500	3 400	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	TILLOTSON HS 298	↑	0.90	15-20	0.50	18"-36"	19.6	3/8"/.404"	1.5 1.6	7.9	—	•/•
3120XP	118.8	60	42.0	6.2 / 9 000	2 500	3 400	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO WG 8	↑	1.25	30-54	0.70	24"-42"	20.1	.404"	1.6	10.4	—	—
371K/375K	70.7/74.7	50/51	36.0	3.5 / 9 000 3.7 / 9 000	2 500	3 600	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO HD 30	↑	0.77	—	—	—	—	—	—	12" 9.4 (371) 14" 9.7 (371-375)	—	—
3120K	118.8	60	42.0	5.8 / 9 000	2 500	3 400	↑	PR 17Y	BPMR 7A RCI 7Y	0.5	SEM CD	0.3	WALBRO WG 9	↑	1.25	—	—	—	—	—	—	14" 13.2 16" 14.0	—	—

Technical Specification 2006 Chain saws, Power cutters

Do not exceed the max no load free speed or engine damage may occur. This figure is for broken in unit. Reduce rpm by 600-700 rpm for a new product.
 ↑ See owners manual and service bulletin.
 (•) Available only in some markets.
 We recommend Husqvarna 2T-fuel and Husqvarna XP-oil.