



Model	Displacement Cylindrada	Bore Alésage Diámetro de cilindro	Stroke Course Carroera	Max power of speed Pissance max. à Potencia máxima a	Idling speed Régime de ralenti Regimen de ralentí	Engagement Régime d'embrayage Regimen de acoplamiento	No load free speed Nombre de tours max. A máxima revolución	Spark plug Bougie Buja	Husqvarna Champion	Electrode gap Ecartement des electrodes Distancia entre electrodos	Ignition system Système d'allumage Sistema de encendido	Air gap Ecartement Distancia	Type of carburetor and setting Carburateur et réglage Carburador y réglaje	Fuel tank volume Débit du réservoir de carburant Capacidad del tanque de combustible	Oil pump capacity Débit de la pompe à huile Capacidad de la bomba de aceite	Oil tank volume Débit du réservoir d'huile Capacidad del tanque de aceite	Bar length Longueur de guide Longitud de la espada	Chain speed Vitesse de chaîne Velocidad de la cadena	Chain pitch Pas de chaîne Paso de la cadena	Drive link gauge Mailloons Eslabones	Weight Poids Peso	Rated voltage Tension nominale Voltaje de régimen	Heated handles / carburetor heating Calentador de las manijas / Calentador eléctrica del carburador Pompas calentantes / Calentaje eléctrica du carburateur
	cu.in cc	Ø inch Ø mm	inch mm	kW rpm	rpm	rpm	rpm	Husqvarna Champion	inch mm	type	inch mm	type	US pint liters	ml/min (9 000rpm)	US pint liters	inch	m/sec	inch	inch mm	lbs. kg	volt	• / •	
316 Electric	—	—	—	1.6	—	—	—	—	—	—	—	—	—	5 (7 500)	0.21 0.10	12"-16"	14.0	3/8"	.050 1.3	8.4 3.8	110 - 120	—	
334T	2.15 35.2	1.50 38	1.22 31.0	1.5 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C1Q-EL33A	0.72 0.34	3-7	0.32 0.15	12"-14"	18.3	3/8"	.050 1.3	7.7 3.5	—	
338XPT	2.40 39.0	1.60 40	1.22 31.0	1.7 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C1Q-EL33A	0.72 0.34	3-7	0.32 0.15	12"-16"	18.3	3/8"	.050 1.3	7.7 3.5	—	
336	2.15 35.2	1.50 38	1.22 31.0	1.5 / 9 600	2 800	4 100	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C1Q-EL20B	0.76 0.36	3-7	0.42 0.16	13"-18"	18.3	.325"	.050 1.3	8.6 3.9	—	
137 e-series	2.22 36.3	1.50 38	1.26 32.0	1.5 / 9 000	3 000	4 500	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	HDA	.012 0.3	ZAMA W29	0.87 0.41	6-8	0.42 0.20	13"-15"	16.3	.325" / 3/8"	.050 1.3	10.1 4.6	—	
142 e-series	2.44 40.2	1.57 40	1.26 32.0	1.6 / 9 000	3 000	4 500	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	HDA	.012 0.3	ZAMA W29	0.87 0.41	6-8	0.42 0.20	13"-15"	16.3	.325" / 3/8"	.050 1.3	10.1 4.6	—	
340	2.49 40.8	1.57 40	1.28 32.5	2.0 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL18B	1.06 0.50	9	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.3 4.7	—	
340 e-series	2.49 40.8	1.57 40	1.28 32.5	2.0 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL32	1.06 0.50	9	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.6 4.8	—	
345 e-series	2.75 45.0	1.65 42	1.28 32.5	2.2 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL32	1.06 0.50	9	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.6 4.8	—	
346XP	2.75 45.0	1.65 42	1.28 32.5	2.5 / 9 600	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL18B	1.06 0.50	5-12	0.59 0.28	13"-20"	18.5	.325"	.050 .058 .063 1.3 1.5 1.6	10.6 4.8	—	• / •
350	3.15 51.7	1.77 45	1.28 32.5	2.3 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL32	1.06 0.50	5-12	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.6 4.8	—	—
353	3.15 51.7	1.77 45	1.28 32.5	2.4 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA C3-EL18B	1.06 0.50	5-12	0.59 0.28	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	11.0 5.0	—	• / •
55 Rancher	3.25 53.2	1.81 46	1.26 32.0	2.5 / 9 000	2 500	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	FHP ET	.012 0.3	ZAMA C1Q-EL7	1.27 0.60	9	0.63 0.30	13"-20"	17.4	.325" / 3/8"	.050 .058 .063 1.3 1.5 1.6	11.4 5.2	—	—
455 Rancher	3.39 55.5	1.85 47	1.26 32	2.5 / 9 000	2 700	3 800	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO WTA5672	0.93 0.44	12	0.32 0.68	13"-20"	17.4	.325" / 3/8"	.058 1.5	12.8 5.8	—	—
357XP	3.45 56.5	1.81 46	1.34 34.0	3.2 / 9 600	2 700	3 700	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 199A	1.43 0.68	6-17	0.80 0.38	13"-24"	21.4	.325" / 3/8"	.050 .058 .063 1.3 1.5 1.6	12.1 5.5	—	• / •
359	3.60 59.0	1.85 47	1.34 34.0	2.9 / 9 000	2 700	3 700	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 199A	1.43 0.68	6-17	0.80 0.38	13"-24"	20.0	.325" / 3/8"	.050 .058 .063 1.3 1.5 1.6	12.1 5.5	—	• / •
365 Special	3.97 65.1	1.89 48	1.42 36.0	3.4 / 9 300	2 700	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 12B	1.63 0.77	6-24	0.89 0.40	15"-28"	20.7	3/8"	.050 .058 .063 1.3 1.5 1.6	13.2 6.0	—	—
570	4.14 67.9	1.93 49	1.42 36	3.6 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA EL28	1.48 0.7	6-24	0.78 0.37	16"-28"	21.4	3/8"	.050 .058 .063 1.3 1.5 1.6	14.9 6.8	—	—
372XP	4.31 70.7	1.97 50	1.42 36.0	3.9 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 12B	1.63 0.77	6-24	0.89 0.40	15"-28"	21.4	3/8"	.050 .058 .063 1.3 1.5 1.6	13.4 6.1	—	• / •
575XP	4.48 73.5	2.01 51	1.42 36	4.0 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	ZAMA EL28	1.48 0.7	6-24	0.78 0.37	16"-28"	21.4	3/8"	.050 .058 .063 1.3 1.5 1.6	14.9 6.8	—	• / •
385XP	5.20 84.7	2.10 54	1.50 37.0	4.6 / 9 600	2 700	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	TILLOTSON HS 296A	1.90 0.90	6-24	1.06 0.50	18"-28"	21.4	3/8"	.058 1.5	15.4 7.0	—	• / •
395XP	5.71 93.6	2.20 56	1.50 38.0	5.2 / 9 600	2 500	3 400	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	TILLOTSON HS 298A	1.90 0.90	15-20	1.06 0.50	18"-36"	19.6	3/8" / .404"	.050 .058 .063 1.3 1.5 1.6	17.8 8.1	—	• / •
3120XP	7.25 118.8	2.36 60	1.65 42.0	6.2 / 9 000	2 500	3 400	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO WG7A	2.64 1.25	30-54	1.45 0.70	24"-42"	20.1	.404"	.063 1.6	22.9 10.4	—	—
371K	4.30 70.7	1.97 50	1.42 36.0	3.5 / 9 000	2 500	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 30	1.63 0.77	—	—	—	—	—	—	12" 20.7/9.4 14" 21.4/9.7	—	—
375K	4.56 74.7	2.02 51	1.42 36.0	3.7 / 9 000	2 500	3 600	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 30	1.63 0.77	—	—	—	—	—	—	14" 21.4/9.7	—	—
3120K	7.25 118.8	2.36 60	1.65 42	5.8 / 9 000	2 500	3 400	↑	PR 17Y	BPMR 7A RCJ 7Y	.02 0.5	SEM ET	.012 0.3	WALBRO WG 9	2.64 1.25	—	—	—	—	—	—	14" 29.1/13.2 16" 30.9/14.0	—	—

## Technical Specification EPA 2006 Chain saws, Power cutters

Do not exceed the max no load free speed or engine damage may occur. This figure is for broken in unit. Reduce rpm by 600-700 rpm for a new product.  
 † See owners manual and service bulletin.  
 We recommend Husqvarna 2T-fuel and Husqvarna XP-oil.